HellermannTyton



Article Number: 151-27009

Description: Low Profile Rivet Mount .938"X.47"-PA66, NA, Mnt Hole

.25", Max Pan .134", T18-T50 Ties, 500/pk

Base Data		
	Local Order Number	LKCRF19H4
	Туре	LKCRF1
	Color	Natural (NA)
	Features and Benefits	 The low-profile rivet mount is designed to secure wiring bundles and fastens with the drive rivet through a predrilled hole. This mount is ideal for use in applications where space is limited.
	Quantity Per	bag
	Product Description	HellermannTyton's Mounts with Rivets are ideal for use in applications where space is limited and is designed to secure wiring bundles. Fastens with the drive rivet through a predrilled hole.
	Short Description	Low Profile Rivet Mount .938"X.47"-PA66, NA, Mnt Hole .25", Max Pan .134", T18-T50 Ties, 500/pk
Product Dimensions		
	Length L (Imperial)	0.938"
	Length L (Metric)	24.0mm
	Fixation Method	with Rivet (Mounts)
	Width W (Imperial)	0.47"
	Width W (Metric)	12.0mm
	Cable Tie Width Max. (Imperial)	0.18"
	Cable Tie Width Max. (Metric)	4.8mm
	Height H (Imperial)	0.157"
	Height H (Metric)	4.0mm
	Panel Thickness Max. (Imperial)	0.134"
	Panel Thickness Max. (Metric)	3.40mm
	Mounting Hole Diameter D (Imperial)	0.25"
	Mounting Hole Diameter D (Metric)	6.5 mm

generated on: 4/28/2017

151-27009



Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Metric)	500Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces

generated on: 4/28/2017